



Delock External Enclosure M.2 SSD 60 mm > SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female

Description

The aluminium enclosure by Delock enables the installation of a M.2 SSD in 2260, 2242 and 2230 format, which can be connected via USB to the PC or laptop.

M.2

Specification

- Connector:
external: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
internal: 1 x 67 pin M.2 key B slot
- Chipset: Asmedia ASM1351
- Supports M.2 modules in format 2260, 2242 and 2230 with key B based on SATA
- Maximum height of the components on the module: 1.35 mm application of double-sided assembled modules supported
- Data transfer rate up to 6 Gbps
- LED indicator for power and access
- Dimensions (LxWxH): ca. 105 x 40 x 10 mm
- Hot Plug, Plug & Play

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6, Mac OS 10.12
- PC or laptop with a free USB Type-A port

Package content

- External enclosure M.2
- Screwdriver
- Mounting material
- USB 3.1 Type-A to USB-C™ cable (ca. 50 cm)
- User manual

Item no. 42573

EAN: 4043619425730

Country of origin: China

Package: Box

Images





General	
Function:	standard Hot Plug Plug & Play
Supported operating system:	standard Linux Kernel 2.6 Mac 10.8.2 Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit
Supported module:	standard M.2 modules in format 2260, 2242 and 2230 with key B or key B+M based on SATA
Maximum height of the components on the module:	standard 1.35 mm application of double-sided assembled modules supported
Interface	
External:	standard 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
Internal:	standard 1 x 67 pin M.2 key B slot
Technical characteristics	
Chipset:	standard Asmedia ASM1351
Data transfer rate:	standard 6 Gb/s
Physical characteristics	
Length:	standard 105 mm
Width:	standard 40 mm
Height:	standard 10 mm
Colour:	standard black