

Straight Blade Devices,
Receptacles, Duplex, Industrial
Grade, 2-Pole 3-Wire Grounding,
20A 125V, 5-20R, Black, Single Pack

By Hubbell Wiring Device-Kellems
Catalog # [HBL5352BK](#)



Straight Blade Devices, Receptacles, Duplex, Industrial Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5-20R, Black, Single Pack.

Features

- Slender/compact design
- Brass Mounting Strap
- Triple wipe contacts

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94 V-0
- Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #12-#10 AWG stranded or solid copper wire only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

General

Catalog Number	HBL5352BK
Color	Black
EU RoHS Indicator	Yes
Horsepower - Maximum	1
Item Type	Traditional Duplex
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Series	Heavy Duty
Specifications	• Automatic Self-grounding Clip - Stainless steel • Base - RTP • Contacts - Brass • Face - Nylon • Mounting Screws - Steel-Zinc Plated • Mounting Strap - .031" (.8) Brass • Terminal Screws - Brass

Style	• Wire Clamp - Plated brass
UPC	Finder Groove Face 783585435008

Dimensions

Dimensions	3.28 in x 1.33 in x 1.05 in
Display Size	Standard Sized Product
Height	1.05 in
Length	3.28 in
Weight	0.2 lb
Width	1.33 in

Electrical Ratings

Amperage Rating	20 A
Connectivity	Back and Side Wired Screw Terminals
Current / Amperage Rating	20 A
Current Rating	20 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 VAC
Voltage Rating Description	125 V
Wattage	2500 W

Conductor Related

Number Of Wires	3-Wire
Wire Size	#12 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s)	• Certified to CSA 22.2, No. 42 File 285 • Fed. Spec. W-C596G • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186
Nema Rating	5-20R
Standards - RoHS Compliance Status	CM

Logistics

Carton Quantity 10
Pallet Quantity 3600

Product Assets

Catalog Page - WDK A-11 Catalog Page
Catalogs - WDK Catalog Full 2024
Engineering Drawing - HBL5352BK AutoCAD Drawing

Installation Manuals - WIRING_PD2615_INSTALLINST
Literature - Wiring Device Solutions for Strategic Manufacturing Facilities
Literature - Entertainment Product Solution Guide
Sales Drawings - WDK_HBL5352_DRAWINGS_PDF
Specifications - HBL5352BK Specification Sheet French
Specifications - Wiring HBL5352BK Specification Sheet
Warranty - Industrial & Commercial Products

