

Rittal – The System.

Faster – better – everywhere.

► Network/server rack VX IT with vented doors, with 482.6 mm (19") mounting angles, standard – VX 5303.114

Date : Aug 17, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Network/server rack VX IT with vented doors, with 482.6 mm (19") mounting angles, standard – VX 5303.114

created: 17.08.2020 on www.rittal.com/com-en



Product description

Material: Sheet steel
Aluminium

Surface finish: Enclosure frame: Dipcoat-primed
Interior installation: Spray-finished
Rear door and roof: Dipcoat-primed, powder-coated
Front door: Aluminium, anodised/spray-finished

Colour: Enclosure frame, rear door and roof: RAL 7035
Front door: Vertical sections, silver coloured and horizontal sections, RAL 9005
Interior installation, vent grille at the front: RAL 9005
Handle and hinges: RAL 9005

Supply includes: VX enclosure frame with doors and roof plate
Aluminium/sheet steel door at the front, vented (vented surface area approx. 85% perforated), 180° hinges
Sheet steel rear door, vented (vented surface area approx. 85% perforated)
Lock front and rear: Comfort handle for profile half-cylinders and security lock 3524 E
Spacers, height 50 mm, to raise the cover plate above the fan cut-out in the roof plate, for passive cooling (supplied loose)
12 x 482.6 mm (19") fastener, 1 U, conductive (supplied loose)
25 multi-tooth screws, conductive (supplied loose)
IPPC pallet
Sheet steel door, vented, one-piece, 130° hinges
Roof plate, multi-piece, with side cable entry in the depth, double-sided, prepared for fan mounting plate

Note: Depending on how and where it is sited, the door opening angle may vary for selected applications

Basic material: Sheet steel

Product features

Dimensions:	Width: 800 mm Height: 1200 mm Depth: 800 mm
Installation height for components:	24 U
Distance between levels as delivered:	520 mm
482.6 mm (19") version:	front and rear
Free mounting space to the 482.6 mm (19") level, front/rear:	150 mm / 130 mm
Load capacity:	8000 N Static (max.) per enclosure to UL 2416: 8000 N
Packs of:	1 pc(s).
EAN:	4028177944831
Customs tariff number:	94032080
ETIM 7.0:	EC011217
ETIM 6.0:	EC002499
eCl@ss 8.0/8.1:	27180207
eCl@ss 6.0/6.1:	27180207
Product description:	VX IT, 19" mounting angles, standard, front and rear, vented, WHD: 800 x 1200 x 800 mm, 24 U

Approvals

Approvals:	UL + C-UL
Declarations:	Declaration of conformity