

Rittal – The System.

Faster – better – everywhere.

Socket strips for IEC 320 connectors – DK 7240.201

Date : Jan 25, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Socket strips for IEC 320 connectors – DK 7240.201

created: 25.01.2018 on www.rittal.com/com-en



Product description

Description:	Socket strips in an aluminium duct.
Benefits:	Practical, universal fastening Providing flexibility and saving on warehousing. In the the 482.6 mm (19") section there is adequate space to route the infeed between the socket strip and the mounting angle without kinks
Material:	Aluminium section, natural anodised Socket inserts: Polycarbonate
Standards:	Sockets: DIN VDE 0620-1
Supply includes:	Socket strip Two mounting brackets Assembly parts
Note:	Depending on the application, we recommend use of a charging current reserve to prevent incorrect activation due to starting-current spikes Variable attachment distance within a range of 25 mm, the distance given is hole centre – hole centre of mounting bracket

Product features

Design:	With IEC 320 input
Dimensions:	Height: 44 mm Depth: 44 mm Length: 482.6 mm

Installation options:	Components with a 25 mm pitch pattern
-----------------------	---------------------------------------

IT wall-mounted distributor, at the rear, horizontal (adequate width provided)
 Enclosure frame
 482.6 mm (19") level

Mounting dimensions:	452.5 mm Tolerance: ± 25 mm
Type of electrical connection:	IEC 60320: C14
Rated voltage:	250 V AC
Rated current (max.):	10 A
Equipment (electrical):	Number of sockets: 9 Jack/socket (type): IEC 320 socket C13 No. of sockets and type: 9 x C13 Colour of socket: Black
Packs of:	1 pc(s).
Weight/pack:	0.61 kg
EAN:	4028177237544
Customs tariff number:	85369095
ETIM 6.0:	EC000330
ETIM 5.0:	EC000330
eCl@ss 8.0/8.1:	27142604
eCl@ss 7.0/7.1:	27142604
eCl@ss 6.0/6.1:	27142604
eCl@ss 5.1/5.1.4:	27143401
Product description (long):	DK Socket strip, IEC 320 socket C13, 9-way, 250 V, 10 A, LHD: 482,6x44x44 mm, For IEC 320 connectors with IEC 320 input
Approvals	
Certificates:	EAC
Declarations:	Declaration of conformity