



MATERIAL RoHS COMPLIANT:

1.CABLE:

CONDUCTOR: 30AWG SOLID SILVER PLATED COPPER.
 INSULATION: FOAM POLYOLEFIN.
 PAIR: 2 SINGLES LAID FLAT AND PARALLEL.
 PAIR DRAIN WIRE: 30AWG SOLID TIN PLATED COPPER.
 PAIR SHIELD: ALUMINUM/POLYESTER TAPE.
 ALUMINUM SIDE FACING IN, 25% OVERLAP.
 DIFFERENTIAL IMPEDANCE: 100±5 OHMS @TDR
 UL RECOGNIZED: AWM STYLE 21490 80°C 30 VOLTS.

2.CONNECTOR:

P0: Mini SAS HD 4i CABLE PLUG (SFF-8643)
 (1) P.C.B: 4 LAYERS, GOLD PLATING ON CONTACT PADS
 (P/N: MPCB-040115NLF REV.A / MPCB-040116NLF REV.A)
 (2) HOUSING: PBT, COLOR: BLACK.
 P1-P4: SATA 7P LOW PROFILE R/A REC.(USAT-F073RA0E)

DELLOCK we move the world	
Title:	Cable Mini SAS HD SFF-8643 > 4 x SATA 7 Pin angled 1 m
Item no.	85685
Barcode	4043619856855

Date	2018 / 06 / 07
Unit	mm
Projection	
Rev	A