



RECOMMENDED  
CABLE STRIPPING DIM'S

STAMP (IF ANY)

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
  2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  3. PHOSPHOR BRONZE PER QQ-B-750
  4. GOLD PL. 3 MIN THICK OVER NICKEL PL 100 MIN. THICK OVER COPPER STRIKE
  5. TEFLON MIL-P-19468
  6. JIS H3250, C 2700

1. CRIMPED FERRULE  
HEX CRIMP SIZE .255"
2. CRIMPED CONTACT PIN  
HEX CRIMP SIZE .068"

DIMENSIONS ARE IN MILLIMETERS				PART NO.						
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				B6121A1-NT3G-3-75						
				APPROVED	DATE					
				CHECKED	DATE					
				DRAWN	DATE					
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	3/1	ISSUE	A	FILE NO.

<h1>Amphenol</h1>	
TITLE BNC CRIMP JACK	
DRAWING NO. KJ-B6121A1-NT3G-62AU-75	
ITEM NO.	

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	
6	FERRULE		NOTE 6	NOTE 2	1	FR-75/66X127
5	INSULATOR	DELTRIN	NATURAL		1	B50000-11-36/1
4	CONTACT PIN		NOTE 3	NOTE 4	1	B74000-8-25/076
3	INSULATOR		NOTE 5	NATURAL	1	B74000-3T-75
2	BODY		NOTE 1	NOTE 2	1	B74000-2
1	HOUSING		NOTE 1	NOTE 2	1	B70000-1-56/39