



TENIO™ Splice Tray for small closures (B6 size) for up to 12 heat shrink splice protectors (SMOUV 45 mm)

- Splice sub-assemblies consists of a wraparound groove plate holding the included splice organizer trays
- Groove plates are designed with slots for routing fiber to and from the organizer trays
- Loop-back facility allowing for single circuit uncut looped fiber storage on the splice tray
- Compliant with most splice types and independent of any optical fiber construction

Product Classification

| | |
|------------------------------|----------------------|
| Product Type | Fiber splice tray |
| Product Series | TENIO |
| Regional Availability | EMEA Latin America |

General Specifications

| | |
|---|--------------------|
| Color | Gray |
| Package, quantity | 12 |
| Packaging Type | Bag Carton |
| Splice Protector Diameter, maximum | 5.00 mm 0.20 in |
| Splice Protector Diameter, minimum | 3.50 mm 0.14 in |
| Splice Protector Length, maximum | 45.00 mm 1.77 in |
| Splice Protector Length, minimum | 35.00 mm 1.38 in |
| Splice Tray Chip Type | Heat shrink |
| Splice Tray Included, quantity | 1 |
| Splices per Tray, quantity | 12 |

Dimensions

| | |
|---------------|-------------------|
| Weight | 0.10 kg 0.22 lb |
|---------------|-------------------|

Mechanical Specifications

| | |
|--------------------------------------|--------------------|
| Material Type | PBT PET |
| Minimum Bend Radius, standard | 30.00 mm 1.18 in |

Environmental Specifications

| | |
|----------------------------|--------------------------------------|
| Environmental Space | Outdoor |
| Storage Temperature | -40 °C to +70 °C (-40 °F to +158 °F) |

Regulatory Compliance/Certifications

Agency
RoHS 2011/65/EU

Classification
Compliant