



MP-88U-F-5 | 6-554720-2

**Modular Plug Kit, 8P/8C, unshielded, flat oval, 2.54 x 8.89 mm max cable jack OD, 8-position, 500/bag**

## Body Features

Conductor Type Solid | Stranded

## Configuration Features

Number of Positions 8  
Keyed No

## Contact Features

Contact Base Material Phosphor bronze  
Contact Mating Area Plating Material Gold  
Contact Mating Area Plating Thickness 50.00  $\mu\text{in}$  | 1.27  $\mu\text{m}$   
Number of Contacts Loaded 8

## Dimensions

Cable Jacket Outside Diameter Range 0.10–0.35 in | 2.54–8.89 mm  
Conductor Outside Diameter 0.034–0.039 in | 0.86–0.99 mm  
Conductor Wire Size 26–24 AWG

## Housing Features

Housing Material Glass filled polycarbonate

## Industry Standards

UL Flammability Rating UL 1863

## Packaging Features

Packaging Quantity 500

## Product Availability

Region Asia | Australia/New Zealand | EMEA | Latin America | North America

## Product Type Features

Cable Type Flat oval, unshielded  
Performance Category Category 5  
Connector Style Plug  
Jack Type RJ45

MP-88UF-5 | 6-554720-2

Latch Style	Standard
Product Type	Connector
Shielded	No

## Termination Features

Termination Method to Wire/Cable	Insulation Displacement Crimp (IDC)
----------------------------------	-------------------------------------