

Product Information




Vertical single-phase BKT Power Distribution Unit with 24 x IEC320 C13 sockets, plug IEC 60309, ammeter with overload alert + 2 automatic fuses with LED indicator


No. Card PI_11340844.24-2_01.16

Power Distribution Units (PDU) have been designed for telecommunications cabinets. A modular, multi-functional design allows the unit to be used in various applications depending on each user's needs. There is a wide range of input plug standards and unit output sockets, as well as control and safety modules. The units are intended for vertical installations. A housing provided for tool free assembly with 'L-Z' type default brackets or brackets dedicated for BKT 4DC cabinets comes as standard.



Features

Index no.	11340844.24-2
Plug	IEC 60309 32A/250V
Cable	H05VV-F 3 x 6.0 mm ² , 3.0 m, black
Sockets	24 x IEC320 C13 10A/250V
Additional components	Ammeter with sound overload alert 2 x automatic fuses with LED indicator
Maximum unit load	32A
Unit rated power	7360 W
Dimensions (L x W x H) [mm]	1182 x 68 x 44.4
Housing	0U, black plastic
Tool-free brackets for BKT 4DC cabinets (must be ordered separately)	
Included default tool-free brackets type: L - Z	
Power plug IEC 60309 32A/250V	

SOCKETS 10A/250V  IEC 320 C13	CABLE LENGTH 3.0 m
RATED POWER 7.4 kW	WARRANTY 3 YEARS