

## Product Information

19" BKT Power Distribution Unit with sockets 6 x DIN 49440 (schuko), plug DIN 49441, red backlit switch with cover + surge protection module with filter

No. Card PI\_1134L016.06-0\_02.17



Power Distribution Units (PDU) have been designed for 19" standard telecommunications cabins. A modular, multi-functional design meets demands of each users. There is a wide range of input plug standards and unit output sockets, as well as control and safety modules. The units are intended mainly for panel installations in the 19" system. However, it is also possible to mount the device vertically or outside the cabinet with special brackets (e. g. to the floor). The housing is made of white aluminium. M6 screws with nuts in a box with washers are attached to each PDU.




## Standards

PN-EN 60950-1; PN-EN 61643-11; PN-IEC 60884-1, EN 62321-1

## Features

Index no.	1134L016.06-0
Power plug	DIN 49441 (unischuko) 16A/250V
Cable	H05VV-F 3 x 1,5 mm <sup>2</sup> , 2.5 m, black
Sockets	6 x DIN 49440 16A/250V
Additional components	Red backlit switch with cover, surge protection module with filter
Lightning protection module	3 x LED indicators
Maximum unit load	16A
Unit rated power	3680 W
Dimensions (L x W xH) [mm]	485 x 44 x 45
Housing	1U, 19", anodized aluminium
Fixed brackets	
Power plug view	

SOCKETS 16A/250V  NF C61-314	CABLE LENGTH  <b>2.5 m</b>
RATED POWER  <b>3.7 kW</b>	WARRANTY  <b>5 YEARS</b>
	MAXIMUM POWER ABSORPTION  <b>240 J</b>