


## RKUB



### Properties:

Temperature range	-30°C to +70°C
Voltage Rating	60 V

### Standards:

Conductor	IEC 60228,5
Construction	EN 50363,3
Flame retardant	IEC 60332-1-2

### Applications:

RKUB is a PVC insulated low voltage flexible conductor. Suitable for use in cars, trucks, trailers and boats.

### Construction

Conductor	Bare or tinned flexible copper conductor
Insulation	PVC
Color	Customers choice
Package	Boxwire, bobbin, coil, drum

Type Code	Cross-section [mm]	Outer diameter [mm]	Copper weight [kg/km]	Total weight [kg/km]	Packing
RKUB	0,5	1,7	4,8	7	Customers choice
RKUB	0,75	1,9	7,2	10	Customers choice
RKUB	1	2,1	9,6	13	Customers choice
RKUB	1,5	2,5	14,4	19	Customers choice
RKUB	2,5	3,0	24,0	30	Customers choice
RKUB	4	3,5	38,4	46	Customers choice
RKUB	6	4,1	57,6	66	Customers choice
RKUB	10	6,0	96,0	81	Customers choice
RKUB	16	7,0	153,6	124	Customers choice
RKUB	25	8,6	240,0	195	Customers choice
RKUB	35	9,9	336,0	289	Customers choice
RKUB	50	11,9	480,0	402	Customers choice
RKUB	70	13,8	672,0	561	Customers choice