

# Delock Network cable M12 8 pin X-coded to RJ45 Hirose plug TPU 1 m

## Description

This industrial Ethernet cable by Delock can be used to connect various components with M12 connectors, e.g. for machine control or automation.

### Durable TPU cable jacket

The material of the cable jacket makes the cable flexible and durable, making it suitable for use in drag chains and harsh environments.

The cable is oil and UV resistant and meets the high requirements for industrial applications.



1 m

## Special features

- Patch cable

## Specification

- Connectors:
  - 1 x M12 male 8 pin X-coded >
  - 1 x RJ45 Hirose plug
- Cat.6A specification
- Suitable for drag chains
- S/FTP
- Shielding: aluminium foil, tinned copper braiding
- Copper cable
- Cable gauge: 26 AWG
- Cable diameter: ca. 6.4 mm
- Cable jacket material: PUR (TPU)
- Max. number of bending cycles: 1,000,000
- Smallest bending radius:
  - 32 mm with fixed installation
  - 64 mm with flexible installation
- Oil-resistant according to DIN EN 60811-2-1
- UV-resistant
- LSOH (halogen-free)
- Flammability class: FT2
- Operating temperature: -20 °C ~ 80 °C
- Protection class: IP20
- Colour: water blue
- Length incl. connectors: ca. 1 m

## Package content

- A free M12 female port
- A free RJ45 jack


## Item no. 85429

EAN: 4043619854295

Country of origin: China

Package: Zip poly bag

Images



**General**

Specification: **standard**  
Cat. 6A

Protection category: **standard**  
IP20

**Interface**

Connector 1: **standard**  
1 x M12 Stecker

Connector 2: **standard**  
1 x RJ45 plug

**Technical characteristics**

Operating temperature: **standard**  
-20 °C ~ 80 °C

**Physical characteristics**

Cable diameter: **standard**  
6.4 mm

Conductor material: **standard**  
copper

Conductor gauge: **standard**  
26 AWG

Shielding: **standard**  
S/FTP

Length: **standard**  
1 m

Smallest bending radius: **standard**  
32 mm

Colour: **standard**  
water blue