

# Delock Media Converter 10/100/1000Base-T to 100/1000Base-X SFP

## Description

This Gigabit Ethernet Media Converter by Delock can be used to expand a network with an optical fiber interface. In the SFP slot, an optional 100 Mb/s or 1 Gb/s SFP module can be used.



## Specification

- Connectors:
  - 1 x SFP slot for 100/1000Base-X SFP module (SFP module not included)
  - 1 x RJ45 jack for 10/100/1000 Mb/s Base-T
  - 1 x DC jack 5.5 x 2.1 mm (power)
- Data transfer rate up to 1 Gb/s
- 6 LEDs for status monitoring
- DIP-switch for configuration of LFP (Link Fault Pass Through)
- Supports IEEE 802.3 / 802.3u / 802.3ab / 802.3z
- Power consumption: 2.5 W
- Metal housing
- Fanless
- Operating temperature: 0 °C ~ 55 °C
- Dimensions (LxWxH): ca. 94 x 70 x 26 mm

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.2 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 2.1 mm
  - outside: ø ca. 5.5 mm
  - length: ca. 9.5 mm

## System requirements

- 100/1000Base-X SFP module
- Device with one free RJ45 port

## Package content

- Media Converter
- Power supply
- User manual

## Item no. 86110

EAN: 4043619861101

Country of origin: China

Package: White Box

Images



Interface	
Output:	<b>standard</b> 1 x SFP slot
Input:	<b>standard</b> 1 x 5 V DC female 5,5 mm x 2,1 mm 1 x RJ45 jack
Technical characteristics	
Data transfer rate:	<b>standard</b> Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps
Physical characteristics	
Housing colour:	<b>standard</b> black
Housing material:	<b>standard</b> metal
Length:	<b>standard</b> 94 mm
Width:	<b>standard</b> 70 mm
Height:	<b>standard</b> 26 mm
Power supply	
Type:	<b>standard</b> Euro wall power supply
Input:	<b>standard</b> AC 100 - 240 V / 50 - 60 Hz / 0.25 A
Output:	<b>standard</b> 5 V / 1.25 A
Connector:	<b>standard</b> DC male 5.5 mm x 2.1 mm