CSB11 FTTH Customer Outlet SC Simplex / LC Duplex Datasheet







G 360° view available for this product - visit the product page online to find out more

The internal customer outlet box is designed for use inside the home. The operator has the choice to have the box unloaded or equipped with adaptors, the box is designed with integrated shutters to comply with safety standards.

Features

- Multiple cable entry points
- Integrated heat shrink splice holder
- Hinged splice Tray
- Holds up to 2 single fibres 1 X SC Simplex or 1 x LC Duplex
- Integrated fibre management
- Integrated shutter protects against laser exposure and dust

Applications

FTTH

Specification

PRODUCT SPECIFICATION	VALUE
Maximum Single Fibre Count	2
Maximum Number of heat splice	2
Number of cable entre points	4
Height	86mm
Width	116mm
Depth	23mm
Colour	White
Material	ABS
Flame Retardant	Yes

Ordering Information

DESCRIPTION

FTTH User outlet unloaded CSB11

SCAN QR FOR PRODUCT PAGE

Further Information



- For additional information please contact your sales representative
- To view the product 360 visit the product page (Scan the QR code or visit the link below)
- Downloaded from
- http://www.fibrefab.com/products/termination-boxes/csb011-ftth-customer-outlet-sc-simplex-lc-duplex/linear-outlet-sc-simplex-lc-duplex-lc-d
- FibreFab reserves the right to make changes to the product specifications in this datasheet at any time without notice
- Information in this document is correct as of March 12, 2015

Europe

- **+** +44 870 127 3330
- sales@fibrefab.com

© FibreFab 2015

Americas

- **+** 1 410 242 9026
- sales@fiberfabinc.com

Middle East & Africa

- **+** +971 4 443 0168
- mea@optronicsnet.com

Asia Pacific

- **+** +86 755 2561 3694
- asia@fibrefab.com