

Rittal – The System.

Faster – better – everywhere.

Network enclosure TE 8000 – TE 7888.460

Date : May 3, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Network enclosure TE 8000 – TE 7888.460

created: 03.05.2020 on www.rittal.com/com-en



Product description

Benefits:	No frame structure Optimum accessibility Readily dismantled and therefore easily installed Interchangeable door hinge
Material:	Sheet steel Glazed door: Single-pane safety glass, 3 mm
Surface finish:	Mounting frame: Dipcoat-primed Enclosure panels: Powder-coated
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 20
Supply includes:	Self-supporting 482.6 mm (19") mounting frames, front and rear, depth-variable Glazed door at the front, including 130° hinge, designer handle and security lock 3524 E Sheet steel door at the rear, including 130° hinge, security lock 3524 E Base frame with maximum cut-out (for optional population with module plates) Roof plate including concealed cut-out for cable entry and optional fan 4 levelling feet, M10 (supplied loose) 4 spacers, 20 mm (supplied loose) to raise the roof plate Side panels, lockable, including security lock 3524 E
Basic material:	Sheet steel

Product features

Design:	with side panels
Dimensions:	Width: 800 mm

Height: 1200 mm
Depth: 800 mm

Installation height for components:	24 U
Distance between levels as delivered:	495 mm
Load capacity:	4000 N
Packs of:	1 pc(s).
Weight/pack:	74 kg
EAN:	4028177801448
Customs tariff number:	94032080
ETIM 7.0:	EC002499
ETIM 6.0:	EC002499
eCl@ss 8.0/8.1:	27180207
eCl@ss 6.0/6.1:	27180207
Product description:	TE Network enclosure TE 8000, WHD: 800x1200x800 mm, 24 U, With glazed door
Approvals	
Declarations:	Declaration of conformity