

Delock 2-Way Wall Socket with 4 x USB Type-A Charging Port 2 x 2.8 A

Description

This power socket with a side grounding contact by Delock is designed for installation in a double flush-mounted or cavity installation box. In addition to two CEE 7/3 sockets with childproof lock, this power socket side grounding contact offers four USB Type-A charging ports. Thus, smartphones, tablets and similar devices can be charged while the socket is still available.

Suitable for many switch series

The socket is compatible to switch series with 55 x 55 mm frame window sizes. This includes the switch series of well-known manufacturers such as Gira, JUNG, Busch-Jaeger or Merten.



Specification

- Connectors:
 - 2 x power socket CEE 7/3 with childproof lock
 - 4 x USB Type-A charging port max. 2 x 2.8 A
 - 2 x 3 screw terminal for PE, N, L
- Rated current: 16 A / 250 V~
- Rated power: 4000 W
- USB Charger:
 - Input: AC 250 V / 50 Hz / 0.2 A
 - USB output: max. 5.0 V / 2.8 A total each socket
 - USB output power: max. 14.0 W total each socket
 - Average active efficiency 82.91 %
 - Efficiency at low load (10 %) 78.09 %
 - No-load power consumption 0.095 W
 - Short circuit protection
- Suitable for switch series with 55 x 55 mm frame window size
- Mounting depth: 40 mm
- Suitable for double installation box
- Claw and screw fixing
- Fire retardant plastic housing (UL 94 V-0)
- Dimensions (LxWxH): ca. 151 x 80 x 52 mm
- Colour: white

System requirements

- Mains supply with grounding
- A free standard installation box

Package content

- Power socket
- User manual

Item no. 11475

EAN: 4043619114757

Country of origin: China

Package: Retail Box

Images



General

Mounting type:	standard in-wall
Protection:	standard Input overvoltage protection Short circuit protection

Interface

Connector 1:	standard 1 x 3 pin terminal block screw terminal
Connector 2:	standard 1 x Steckdose CEE 7/3 mit Kindersicherung
connector 3:	standard 2 x USB Type-A female

Physical characteristics

Length:	standard 80 mm
Width:	standard 80.0 mm
Height:	standard 56 mm
Colour:	standard white