

Delock GSM UMTS Antenna N Jack 7 dBi 75.6 cm omnidirectional fixed wall and pole mounting white outdoor

Description

This antenna by Delock allows the usage of GSM UMTS bands indoors and outdoors.



Specification

- Connector: N jack
- Antenna type: Collinear dipole array
- Frequency range:
824 - 960 MHz
1710 - 2170 MHz
- Antenna gain: 7 dBi
- Impedance: 50 Ohm
- Polarisation: vertical
- HBW horizontal beamwidth: 360°
- VBW vertical beamwidth: 6°
- VSWR: 2.0
- Power handling: max. 50 W
- Operating temperature: -40 °C ~ 60 °C
- Body: GFRP UV resistant
- Length: ca. 75,6 cm
- Diameter: ca. 2.6 cm
- Weight:
antenna: ca. 400 g
mounting material: ca. 70 g

System requirements

- Device with a free N connector

Package content

- Antenna
- Mounting material















Item no. 12500

EAN: 4043619125005

Country of origin: Taiwan, Republic of China

Package:

Images



General	
Mounting type:	standard pole wall
Suitable for indoor:	standard yes
Suitable for outdoor:	standard yes
Interface	
connector:	standard 1 x N jack
Technical characteristics	
Frequency range:	standard 0.824 - 0.960 GHz 1.71 - 2.17 GHz
Antenna gain:	standard 7 dBi
Beam width horizontal:	standard 360°
Beam width vertical:	standard 6°
Impedance:	standard 50 Ω
Operating temperature:	standard -40 °C ~ 60 °C
Polarisation:	standard vertical
Power handling:	standard 50 W
Vertical beam form:	standard 6°
VSWR:	standard 2.0
Physical characteristics	
Antenna type:	standard omnidirectional
Housing material:	standard GFRP UV resistant
Weight:	standard 400 g
Diameter:	standard 2.6 cm
Length:	standard 75.6 cm



Colour: **standard**
white