

# Delock External Enclosure 2 x M.2 Key B > SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) with RAID

**M.2**

## Description

The aluminium enclosure by Delock enables the installation of two M.2 SSD in 2280, 2260, 2242 and 2230 format, which can be connected via USB to the PC or laptop. When using more than one SSD, there is the possibility to use different RAID level.



## Specification

- Connector:  
external: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type Micro-B female  
internal: 2 x 67 pin M.2 key B slot
- Interface: SATA
- Chipset: Asmedia ASM1352R
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key B based on SATA
- Maximum height of the components on the module: 1.25 mm application of double-sided assembled modules supported
- Supports RAID 0, 1, SPAN, Port Multiplier
- Switch for RAID mode
- Reset button
- Data transfer rate up to 6 Gb/s
- 2 x LED indicator for power and access
- Operating temperature: 0 °C ~ 70 °C
- Storage temperature: -20 °C ~ 70 °C
- Dimensions (LxWxH): ca. 100 x 80 x 17 mm
- Hot Plug, Plug & Play

## System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6, Mac OS 10.12
- PC or laptop with a free USB Type-A port

## Package content

- External enclosure
- Screwdriver, screws
- Cable USB 3.1 Type-A to Type Micro-B, length ca. 40 cm
- User manual

## Item no. 42588

EAN: 4043619425884

Country of origin: Taiwan, Republic of China

Package: Retail Box

## Images



General	
Function:	<b>standard</b> Hot Plug Plug & Play
Internal construction:	<b>standard</b> full PCB
Supported operating system:	<b>standard</b> Linux Kernel 3.19 Mac OS 10.12 Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit
Supported module:	<b>standard</b> M.2 modules in format 2280, 2260, 2242 and 2230 with key B or key B+M based on SATA
Maximum height of the components on the module:	<b>standard</b> 1.5 mm application of double-sided assembled modules supported
Interface	
External:	<b>standard</b> 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type Micro-B female
Internal:	<b>standard</b> 2 x 67 pin M.2 key B slot
Technical characteristics	
Chipset:	<b>standard</b> Asmedia ASM1352R
Data transfer rate:	<b>standard</b> USB 3.1 Gen 2 up to 10 Gb/s
RAID function:	<b>standard</b> SPAN 0 1 Port Multiplier
Physical characteristics	
Housing material:	<b>standard</b> Aluminium
Length:	<b>standard</b> 100 mm
Width:	<b>standard</b> 80 mm
Height:	<b>standard</b> 17 mm
Colour:	<b>standard</b> black

