



# Delock External Enclosure 2 x M.2 Key B SSD > USB 3.1 Gen 2 USB Type- $C^{TM}$ female with RAID

### Description

The aluminium enclosure by Delock enables the installation of two M.2 SSD in 2280, 2260, 2242 and 2230 format, which can be connected via USB to the PC or laptop. When using more than one SSD, there is the possibility to use different RAID level.



## **Specification**

· Connector:

external: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-CTM female internal: 2 x 67 pin M.2 key B slot

- Chipset: Asmedia ASM1352R
- Supports M.2 modules in format 2280, 2260 and 2242 with key B based on SATA
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Data transfer rate up to 6 Gbps
- · Supports RAID 0, RAID 1, JBOD, Port Multiplier
- LED indicator for RAID mode
- 1 x button for RAID setting
- Compliant with USB Attached SCSI Protocol (UASP) Rev. 1.0
- · Hot Plug, Plug & Play
- · Colour: grey
- Dimensions (LxWxH): ca. 125 x 77 x 15.5 mm

#### System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6, Mac OS 10.12
- PC or laptop with a free USB Type-A port

#### Package content

- External enclosure
- Screws
- Cable USB-C™ male to USB Type-A male, length ca. 50 cm
- User manual

#### **Images**







#### Item no. 42589

EAN: 4043619425891

Country of origin: China

Package: Retail Box





General	
Function:	standard
	Hot Plug
	Plug & Play
Supported operating system:	standard
	Linux Kernel 4.2
	Mac OS 10.9
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
Supported module:	standard
	M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA
Maximum height of the components on	standard
the module:	1.5 mm application of double-sided assembled modules supported
Interface	
External:	standard
	1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
Internal:	standard
	2 x 67 pin M.2 key B slot
Technical characteristics	
Data transfer rate:	standard
	6 Gb/s
RAID function:	standard
	JBOD
	0
	1
	Port Multiplier
Physical characteristics	
Housing material:	standard
	Aluminium
Length:	standard
	125 mm
Width:	standard
	77 mm
Height:	standard
	15.5 mm
Colour:	standard
	grey