

# Delock Adapter USB Type-C™ male > HDMI female (DP Alt Mode) 4K 60 Hz with PD function

## Description

This Delock adapter is suitable for the connection of a HDMI monitor to a computer with USB-C™ interface and Displayport alternate mode support. Thus, the adapter can be connected to different laptops like Macbook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface. The adapter has a USB Type-C™ Power Delivery port. This allows the laptop to be charged while the adapter is in use.



## Specification

- Connectors:
  - Input:
    - 1 x USB Type-C™ male
    - 1 x USB Type-C™ Power Delivery female (optional for power supply)
  - Output:
    - 1 x HDMI-A 19 pin female
- Chipset: VIA VL100 + Parade PS176
- Displayport 1.2 and High Speed HDMI with Ethernet (HEC) specification
- Resolution up to 4096 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Transfer of audio and video signals
- Audio formats: 8-channel LPCM, compressed audio and HBR audio format up to 24 Bit audio sample size and 192 kHz sample rate
- Supports 3D displays
- Supports HDCP 1.4 and 2.2
- Charging power: max. 60 W, 20 V @ 3 A
- USB bus powered
- Plug & Play
- Housing material: aluminium
- 1 x ferrite core
- Cable length without connectors: ca. 20 cm
- Colour: dark grey

## System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Windows 10 Mobile, Chrome OS, Linux ex Kernel 4.3, Mac ex OS 10.12, Android ex 6.0
- PC or laptop with a free USB Type-C™ port and Displayport alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

## Package content

- USB-C™ to HDMI adapter


## Item no. 62988

EAN: 4043619629886

Country of origin: China

Package: Retail Box

Images



| General                     |   |
|-----------------------------|---|
| Function:                   | <b>standard</b><br>Plug & Play  |
| Specification:              | <b>standard</b><br>DisplayPort 1.2<br>High Speed HDMI with Ethernet<br>HDCP 1.4<br>HDCP 2.2   |
| Supported operating system: | <b>standard</b><br>Android ex 6.0<br>Chrome OS<br>Windows 7 32-bit<br>Windows 7 64-bit<br>Windows 8.1 32-bit<br>Windows 8.1 64-bit<br>Windows 10 32-bit<br>Windows 10 64-bit<br>Windows 10 Mobile<br>ex Linux Kernel 4.3<br>ex Mac OS 10.12 |
| Interface                   |   |
| Output:                     | <b>standard</b><br>1 x HDMI-A 19 pin female   |
| Input:                      | <b>standard</b><br>1 x USB Type-C™ female (power supply)<br>1 x USB Type-C™ male  |
| Technical characteristics   |   |
| Chipset:                    | <b>standard</b><br>Parade PS176<br>VIA VL100  |
| Maximum screen resolution:  | <b>standard</b><br>4096 x 2160 @ 60 Hz  |
| Signal transmission:        | <b>standard</b><br>video<br>audio   |
| Physical characteristics    |   |
| Ferrite core:               | <b>standard</b><br>1 x  |
| Housing material:           | <b>standard</b><br>Aluminium  |
| Cable length:               | <b>standard</b><br>20 cm  |
| Connector finishing:        | <b>standard</b><br>nickel-plated  |



Colour: **standard**  
dark grey