

Delock Adapter USB Type-C™ male > mini Displayport female (DP Alt Mode) 4K 60 Hz with PD function

Description

This Delock adapter is suitable for the connection of a Displayport monitor to a computer with USB-C™ interface and Displayport alternate mode support. Thus, the adapter can be connected to different laptops like Macbook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface. The adapter has a USB Type-C™ Power Delivery port. This allows the laptop to be charged while the adapter is in use.



Specification

- Connectors:
 - Input:
 - 1 x USB Type-C™ male
 - 1 x USB Type-C™ Power Delivery female (optional for power supply)
 - Output:
 - 1 x mini Displayport 20 pin female
- Chipset: VIA VL100
- Resolution up to 4096 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Transfer of audio and video signals
- Charging power: max. 60 W, 20 V @ 3 A
- USB bus powered
- Plug & Play
- Housing material: aluminium
- 1 x ferrite core
- Cable length without connectors: ca. 20 cm
- Colour: dark grey

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Windows 10 Mobile, Chrome OS, Linux ex Kernel 4.3, Mac ex OS 10.12
- PC or laptop with a free USB Type-C™ port and Displayport alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- USB-C™ to mini Displayport adapter

Item no. 62990

EAN: 4043619629909

Country of origin: China

Package: Retail Box

Images



General

| | |
|-----------------------------|---|
| Function: | standard Plug & Play |
| Supported operating system: | standard Chrome OS Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Windows 10 Mobile ex Linux Kernel 4.3 ex Mac OS 10.12 |

Interface

| | |
|---------|--|
| Output: | standard 1 x mini DisplayPort 20 pin female |
| Input: | standard 1 x USB Type-C™ female (power supply) 1 x USB Type-C™ male |

Technical characteristics

| | |
|----------------------------|--|
| Chipset: | standard VIA VL100 |
| Maximum screen resolution: | standard 4096 x 2160 @ 60 Hz |
| Signal transmission: | standard video audio |

Physical characteristics

| | |
|----------------------|----------------------------------|
| Ferrite core: | standard 1 x |
| Housing material: | standard Aluminium |
| Cable length: | standard 20 cm |
| Connector finishing: | standard nickel-plated |
| Colour: | standard dark grey |