



# Delock Adapter USB Type-C<sup>™</sup> male > VGA female (DP Alt Mode) + USB Type-A + USB Type-C<sup>™</sup> PD

# Description

This adapter by Delock is suitable for the connection of a VGA monitor to a computer with USB-C<sup>TM</sup> interface and Displayport alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt<sup>TM</sup> 3 interface. Additional the adapter has a USB 3.1 Type-A port and a USB-C<sup>TM</sup> port. The USB-C<sup>TM</sup> port can be used for power supply of the output device or to transfer data in USB 3.1 Gen 1 speed. Different USB devices such as docking stations, card reader, external enclosure etc. can be connected.



Specification

#### Connectors:

- 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ male >
- 1 x VGA 15 pin female
- 1 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female
- 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C<sup>™</sup> Power Delivery female (optional for power supply)
- Chipset: VIA VL101 + VL813 + ITE IT6516
- Displayport 1.1a specification
- Resolution up to WUXGA 1920 x 1200 @ 60 Hz (depending on the system and the connected hardware)
- Transfer of analogue video signals
- USB bus powered
- Plug & Play
- · Gold-plated connectors
- 1 x ferrite core
- · Cable length without connectors: ca. 20 cm
- Colour: grey

#### System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Mac ex OS 10.12.5
- PC or laptop with a free USB Type-C<sup>™</sup> port and Displayport alternate mode or
- PC or laptop with a free Thunderbolt<sup>™</sup> 3 port

### Package content

USB-C<sup>™</sup> to VGA Adapter + USB Type-A

## Images



ltem no. 62992

EAN: 4043619629923

Country of origin: China

Package: Retail Box





General	
Function:	standard
	Plug & Play
Supported operating system:	standard
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	ex Mac OS 10.12.5
Interface	
Output:	standard
	1 x VGA 15 pin female
	1 x USB 3.0 Type-A female
Input:	standard
	1 x USB Type-C <sup>™</sup> female (power supply)
	1 x USB Type-C™ male
Technical characteristics	
Maximum screen resolution:	standard
	1920 x 1200 @ 60 Hz
Physical characteristics	
Cable length:	standard
	20 cm