

Delock External Industry Hub 4 x USB 3.0 Type-A with 15 kV ESD protection

Description

This solid industry capable USB Hub by Delock can be connected to a computer via the USB Type-A interface. It expands the computer by four USB Type-A connectors, which supports the USB Battery Charging specification BC1.2. Thus, connected devices such as smartphones can be charged faster. If necessary, an optional power supply or an optional power cable can be connected to the power socket.



Specification

- Connectors:
 - 1 x USB 3.0 Type-B female >
 - 4 x USB 3.0 Type-A female - Battery Charging specification BC1.2
 - 1 x 9 - 40 V DC jack
 - 1 x 3 pin terminal power connector
- Chipset: VIA VL811+
- Data transfer rate up to:
 - SuperSpeed USB 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- 5 x LED indicator
- USB ports with screw jacks
- Robust metal housing
- Removable wallmount brackets
- Power supply: Bus-powered or Self-powered
- Flexible power supply with 9 V to 40 V
- Automatic detection of the input polarity of the power connectors
- ESD protection up to 15 kV for all ports
- Dimensions (LxWxH): ca. 158 x 80 x 32 mm
- Colour: black
- Plug & Play

Specification of the power jack

- 9 - 40 V
- Dimensions:
 - inside: \varnothing ca. 2.1 mm
 - outside: \varnothing ca. 5.5 mm
 - length: ca. 9 mm

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, ex Linux Kernel 3.16.x, ex Mac OS 10.9
- PC or laptop with a free USB Type-A port

Package content

- Hub USB
- 1 x cable USB A male to USB B male, length ca. 1 m
- 2 x wall mounting brackets
- 1 x 3 pin terminal block

Item no. 63309

EAN: 4043619633098

Country of origin: China

Package: Retail Box

- User manual

Images



- ① 1x USB 3.0 Type-A female
- ② 4x USB 2.0 Type-A female – Battery Charging specification BC1.2
- ③ 1x 3-pin terminal power connector
- ④ 1x 9 – 40V DC jack

General	
Function:	standard Battery Charging BC1.2 Plug & Play
Mounting type:	standard DIN rail Screw mounting
Supported operating system:	standard Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit ex Linux Kernel 3.16 ex Mac OS 10.9
LED indicator:	standard 5 x
Interface	
Connector 1:	standard 1 x USB 3.0 Type-B female
Connector 2:	standard 4 x USB 3.0 Type-A female - Battery Charging specification BC1.2
connector 3:	standard 1 x 9 – 40 V DC jack
connector 4:	standard 1 x 3 pin terminal power connector
Physical characteristics	
Length:	standard 158 mm
Width:	standard 80 mm
Height:	standard 32 mm
Colour:	standard black