



Delock External Industry Hub 10 x USB 3.0 Type-A with 20 kV ESD protection

Description

This solid industry capable USB hub by Delock can be connected to a computer via the USB Type-A interface. It expands the computer by ten USB Type-A connectors. If necessary, an optional power supply or an optional power cable can be connected to the power socket.



Specification

- Connectors:
 - 1 x USB 3.0 Type-B female >
 - 10 x USB 3.0 Type-A female
 - 1 x 9 - 40 V DC jack
 - 1 x 3 pin terminal power connector
- Chipset: VIA VL817
- Data transfer rate up to:
 - SuperSpeed USB 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- 11 x LED indicator
- USB ports with screw holes
- Robust metal housing
- Removable wallmount brackets
- Power supply: Bus-powered or Self-powered
- Flexible power supply with 9 V to 40 V
- Automatic detection of the input polarity of the power connectors
- ESD protection up to 20 kV for all ports
- Dimensions (LxWxH): ca. 202 x 80 x 32 mm
- Colour: black
- Plug & Play

Specification of power connector

- 9 - 40 V
- Dimensions:
 - inside: \varnothing ca. 2.1 mm
 - outside: \varnothing ca. 5.5 mm
 - length: ca. 9 mm

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 3.16.x, Mac ex OS 10.9
- PC or laptop with a free USB Type-A port

Package content

- Hub USB
- 1 x cable USB A male to USB B male, length ca. 1 m
- 2 x wall mounting brackets
- 1 x mounting for 35 mm DIN rail

Item no. 63919

EAN: 4043619639199


Country of origin: China

Package: Retail Box



- 1 x 3 pin terminal block
- User manual

Images





General	
Function:	standard Battery Charging BC1.2 Plug & Play
Mounting type:	standard DIN rail Screw mounting
Supported operating system:	standard Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit ex Linux Kernel 3.16 ex Mac OS 10.9
LED indicator:	standard 11 x
Interface	
Connector 1:	standard 1 x USB 3.0 Type-B female
Connector 2:	standard 10 x USB 3.0 Type-A female - Battery Charging specification BC1.2
connector 3:	standard 1 x 9 – 40 V DC jack
connector 4:	standard 1 x 3 pin terminal power connector
Physical characteristics	
Length:	standard 202 mm
Width:	standard 80 mm
Height:	standard 32 mm
Colour:	standard black