

Delock DisplayPort Adapter for a USB Type-C™ monitor 4K 60 Hz

Description

This adapter by Delock is suitable for the connection of a USB-C™ monitor to a computer with DisplayPort interface. The adapter must be connected to the computer with an existing DisplayPort cable. The signals are transmitted via DisplayPort Alternate Mode.



ca. 20 cm

Specification

- Connectors:
 - 1 x DisplayPort 20 pin female >
 - 1 x USB Type-C™ male
- Chipset: Cypress
- DisplayPort 1.2 specification
- Signal direction: DisplayPort input > USB Type-C™ output
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Transmission of audio and video signals
- Supports 3D displays
- Plug & Play
- Connectors: gold-plated
- 1 x ferrite core
- Cable length without connectors: ca. 20 cm
- Colour: black

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, ex Linux Kernel 4.3.3
- USB Type-C™ monitor
- PC or laptop with a free DisplayPort port
- One DisplayPort cable

Package content

- DisplayPort to USB-C™ adapter

Item no. 63928

EAN: 4043619639281

Country of origin: China

Package: Retail Box

Images



General	
Function:	standard Plug & Play
Specification:	standard DisplayPort 1.2
Supported operating system:	standard Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit ex Linux Kernel 4.3.3
Interface	
Output:	standard 1 x USB Type-C™ male
Input:	standard 1 x DisplayPort 20 pin female
Technical characteristics	
Chipset:	standard Cypress
Maximum screen resolution:	standard 3840 x 2160 @ 60 Hz
Signal transmission:	standard video audio
Physical characteristics	
Ferrite core:	standard 1 x
Cable length:	standard 20 cm
Connector finishing:	standard gold-plated
Colour:	standard black