

Delock USB 3.1 Gen 1 Adapter USB Type-C™ to 3 x USB 3.0 Type-A Hub + 1 x HDMI (DP Alt Mode) 4K 30 Hz

Description

This adapter by Delock is suitable for the connection to a computer with USB-C™ interface and DisplayPort alternate mode support. It extends the system by three USB 3.0 Type-A interfaces as well as one HDMI interface.



Specification

- Connectors:
 - 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ male >
 - 3 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female
 - 1 x HDMI-A 19 pin female
- Chipset: VL100, VL813, PS176
- DisplayPort 1.2, High Speed HDMI with Ethernet (HEC) and SuperSpeed USB specification
- HDMI specification:
 - Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
 - Transfer of audio and video signals
 - Supports 3D displays
 - Supports HDCP 1.4 and 2.2
- USB bus powered
- Plug & Play
- 1 x ferrite core
- Metal housing
- Cable length without connectors: ca. 15 cm
- Colour: black

System requirements

- Android 6.0 or above
- Chrome OS
- Linux Kernel 3.19 or above
- Mac OS 10.12 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- Windows 10 Mobile
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- USB-C™ to 3 x USB-A + HDMI adapter

Item no. 63931

EAN: 4043619639311

Country of origin: China

Package: Retail Box

Images



General	
Function:	standard Plug & Play
Supported operating system:	standard Chrome OS Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Windows 10 Mobile Linux Kernel 3.19 or above Mac OS 10.12 or above
Interface	
Output:	standard 3 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female 1 x HDMI-A 19 pin female
Input:	standard 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ male
Technical characteristics	
Data transfer rate:	standard 5 Gbps
Physical characteristics	
Material:	standard Aluminium
Colour:	standard black
Cable length without connectors:	standard 15 cm