



Delock USB Condenser Microphone Set - for Podcasting, Gaming and Vocals

Description

This USB condenser microphone by Delock can be used for high-quality voice and vocal recordings.

Optimal recordings

The microphone has a cardioid polar pattern (unidirectional) and captures the sound ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

Dual Layer Pop Filter & Windscreen

Due to the included dual layer pop filter and the windscreen, the recording quality is further optimized. Annoying wind noises are optimally filtered.

Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.

Stable & non-slip stand

The metal base with rubber feet ensures that the microphone stands stable on the table. The shock mount (spider) ensures vibration-free recording. The table stand can be folded and transported easily if required.

Specification

- Connector: 1 x USB 2.0 Type-A male
- Directivity: unidirectional
- Sensitivity: -47 dB +/- 3 dB
- Frequency range: 20 Hz 20 kHz
- Sample rate: 16 Bit / 44.1 kHz
- Signal-to-noise ratio (SNR): ca. 60 dB
- Impedance: 2.2 kOhm
- Cable length: ca. 1.5 m
- Colour: black
- Dimensions (LxWxH): ca. 150 x 45 x 35 mm
- USB bus powered
- Plug & Play

System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- Table stand
- Shock mount (spider)
- Pop filter
- Windscreen
- User manual



ltem no. 66331

EAN: 4043619663316 Country of origin: China Package: Retail Box





Images







General	
Function:	standard
	Plug & Play
Supported operating system:	standard
	Chrome OS
	Mac OS 10.9 or above
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8 32-bit
	Windows 8 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Linux Kernel 4.4 or above
Interface	
connector:	standard
	1 x USB 2.0 Type-A male
Technical characteristics	
Frequency range:	standard
	20 Hz - 20 kHz
Voltage:	standard
	USB bus powered
Sensibility:	standard
	- 47 dB +/- 3 dB
Sample rate:	standard
	16 Bit / 44.1 kHz
Signal noise ratio (SNR):	standard
Discretivity	ca. ≥ 60dB
Directivity:	standard
Physical characteristics	uni-directional
Cable length:	standard
	1.5 m
Length:	standard
	150 mm
Width:	standard
	45 mm
Height:	standard
	35 mm
Colour:	standard
	black