



# Delock HDMI Switch 3 x HDMI in to 1 x HDMI out 4K 60 Hz with Audio Extractor

### Description

With this HDMI switch by Delock up to **three HDMI devices** can be used with one HDMI monitor, TV or projector. The button on the device or the remote control can be used to switch between the HDMI devices.

#### Audio extractor

This function can be used to extract the audio signal from an HDMI transmission. While the video signal is displayed on a TV or monitor, the audio signal can be sent **digital (S/PDIF) or analogue (stereo)** to other devices, such as headphones or a surround receiver.

#### Audio Return Channel (ARC)

ARC can be enabled at the push of a button on the device or the remote control. Then the **audio signal of the connected TV** device is routed to the S/PDIF connectors of the switch.

#### Specification

- Connectors:
- Input:
- 3 x HDMI-A female 1 x DC 5 V power connector
- Output:
- 1 x HDMI-A female
- 2 x RCA female (audio)
- 1 x TOSLINK female S/PDIF
- 1 x RCA female S/PDIF
- HDMI port switching: automatic function, via button or via infrared remote control
- LED indicators for active HDMI port
- High Speed HDMI specification
- · Supports 3D displays
- Supports HDCP 1.4 and 2.2
- Supports HDR
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- · Video bandwidth up to 600 MHz / 6 Gbps, max. 18 Gbps
- Power consumption: max. 5 W
- Metal housing
- Removable wallmount brackets
- Colour: black
- Dimensions (LxWxH): ca. 168 x 75 x 21 mm

#### Power supply specification

- · Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- · Ground outside, plus inside
- Dimensions: inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9 mm

#### System requirements

- A free HDMI female
- HDMI cable



ltem no. 66498

EAN: 4043619664986 Country of origin: China Package: Retail Box





## Package content

- HDMI switch
- Remote control
- Mounting brackets and screws
- USB power cable, length: ca. 0.5 m
- · Power supply
- User manual

## Images













General	
	etenderd
Specification:	standard
	High Speed HDMI
	HDCP 1.4
	HDCP 2.2
	HDR
Interface	
Output:	standard
	1 x RCA female
	1 x HDMI-A 19 pin female
	1 x TOSLINK female S/PDIF
	2 x RCA female (red, white)
Input:	standard
	1 x 5 V DC female 5,5 mm x 2,1 mm
	3 x HDMI-A 19 pin female
Technical characteristics	
Maximum screen resolution:	standard
	3840 x 2160 @ 60 Hz
Physical characteristics	
Housing colour:	standard
	black
Housing material:	standard
	metal
Length:	standard
	168 mm
Width:	standard
	75 mm
Height:	standard
	21 mm
Power supply	
Туре:	standard
	Euro wall power supply
Input:	standard
	AC 100 - 240 V / 50 - 60 Hz / 0.5 A
Output:	standard
	5 V / 1 A
Connector:	standard
	DC male 5.5 mm x 2.1 mm