

Delock Cable DC 5.5 x 2.5 mm male to open wire ends 15 cm angled

Description

This terminal block cable by Delock can be used to connect bare wires. Thus the cable is not only convenient for special industry applications, but also for the hobby area, e.g. railway modelling. Various devices with a suitable DC power connector can be connected to the cable and are supplied with power individually (depending on the requirements of the device).



15 cm

Specification

- Connectors:
1 x DC 5.5 x 2.5 mm male angled >
2 x open wires
- Positive pole inside, negative pole outside
- Voltage: max. 12 ~ 36 V
- Current: max. 5 A
- Cable gauge: 23 AWG
- DC pin length: ca. 9.5 mm
- Length without connectors: ca. 15 cm

System requirements

- A free DC female port 5.5 x 2.5 x 9.5 mm

Package content

- Cable

Item no. 85748

EAN: 4043619857487

Country of origin: China

Package: Poly bag

Images





Interface	
connector:	standard 1 x DC 5.5 x 2.5 x 9.5 mm male
Connector 1:	standard 2 x open wires
Technical characteristics	
Maximum current:	standard 5 A
Voltage:	standard max. 12 ~ 36 V
Physical characteristics	
Conductor material:	standard copper
Conductor gauge:	standard 23 AWG
Cable length without connectors:	standard 15 cm