

## Delock Modular Wall Outlet flush mount 2 Port Cat.6 LSA

### Description

This network wall outlet by Delock can be installed in-wall or on a back box with 60 mm mounting holes. The LSA blocks can be used with a punch down tool; the horizontal cable feed allows a flexible installation.



### Specification

- Connectors:
  - external: 2 x RJ45 jack
  - internal: 2 x LSA block
- Cat.6 specification
- Shielded (STP)
- TIA-568A/B pinout
- Cable diameter up to 0.644 mm (22 - 26 AWG)
- Material: zinc die cast
- Integrated name plate
- Design suitable central plate 50 x 50 mm
- Mounting holes 60 mm
- Colour: pure white RAL 9010
- Dimensions (LxWxH): ca. 80 x 80 x 39 mm

### Item no. 86125

EAN: 4043619861255

Country of origin: China

Package: Zip poly bag

### Package content

- Modular Wall Outlet
- 2 screws

### Images



General	
Suitable for conductor gauge:	<b>standard</b> 22 - 26 AWG
Mounting type:	<b>standard</b> in-wall
Interface	
External:	<b>standard</b> 2 x RJ45 Jack
Internal:	<b>standard</b> 2 x LSA block
Technical characteristics	
Category:	<b>standard</b> Cat.6
Shielding:	<b>standard</b> shielded
Physical characteristics	
Housing colour:	<b>standard</b> white
Length:	<b>standard</b> 80 mm
Width:	<b>standard</b> 80 mm
Height:	<b>standard</b> 39.1 mm