



# Delock WLAN 802.11 ac/a/b/g/n Antenna RP-SMA plug 4 - 5 dBi omnidirectional with tilt joint black

## Description

This Wireless LAN antenna can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals.



## Specification

- Connector: RP-SMA plug
- Frequency range:
  - 2.4000 - 2.4835 GHz
  - 5.1500 - 5.7250 GHz
- Antenna gain: 4 - 5 dBi
- Impedance: 50 Ohm
- Polarisation: linear, vertical
- VSWR: 2.0
- Operating temperature: -20 °C ~ 65 °C
- Housing material: TPEE
- Colour: black
- Length:
  - ca. 195.00 mm (with tilt joint)
  - ca. 165.00 mm (without tilt joint)
- Diameter:
  - ca. 6.00 mm (top)
  - ca. 12.50 mm (RP-SMA)

## System requirements

- Device with a free RP-SMA jack

## Package content

- WLAN antenna

## Item no. 88393





EAN: 4043619883936

Country of origin: Taiwan, Republic of China

Package: Poly bag



Images





General	
Suitable for indoor:	<b>standard</b> yes
Interface	
connector:	<b>standard</b> RP-SMA plug
Technical characteristics	
Frequency range:	<b>standard</b> 2.4000 - 2.4835 GHz 5.1500 - 5.7250 GHz
Antenna gain:	<b>standard</b> 4 - 5 dBi
Beam width horizontal:	<b>standard</b> 360°
Impedance:	<b>standard</b> 50 Ω
Operating temperature:	<b>standard</b> -20 °C ~ 65 °C
Polarisation:	<b>standard</b> linear vertical
VSWR:	<b>standard</b> 2.0
Physical characteristics	
Housing colour:	<b>standard</b> black
Housing material:	<b>standard</b> TPEE
Diameter:	<b>standard</b> 12.5 cm
Length:	<b>standard</b> 19.6 cm