

# Delock WLAN 802.11 ac/a/b/g/n Antenna RP-SMA plug 2 - 5 dBi omnidirectional with tilt joint white

## Description

This Wireless LAN antenna can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals.



## Specification

- Connector: RP-SMA plug
- Frequency range:  
2.400 - 2.500 GHz  
5.100 - 5.875 GHz
- Antenna gain:  
2 dBi @ 2.5 GHz  
5 dBi @ 5.7 GHz
- Impedance: 50 Ohm
- Polarisation: linear, vertical
- VSWR: 2.0
- Operating temperature: -10 °C ~ 55 °C
- Housing material: ABS
- Colour: white
- Length:  
ca. 143.00 mm (with tilt joint)  
ca. 109.70 mm (without tilt joint)
- Diameter:  
ca. 18.80 mm (top)  
ca. 10.00 mm (RP-SMA)

## Item no. 88460

EAN: 4043619884605

Country of origin: Taiwan, Republic of China

Package: Retail Box


## System requirements

- Device with a free RP-SMA jack

## Package content

- WLAN antenna

## Images



<b>Interface</b>	
connector:	<b>standard</b> RP-SMA plug
<b>Technical characteristics</b>	
Frequency range:	<b>standard</b> 2.400 - 2.500 GHz 5.100 - 5.875 GHz
Gain:	<b>standard</b> 2 dBi @ 2.5 GHz 5 dBi @ 5.7 GHz
Impedance:	<b>standard</b> 50 $\Omega$
Operating temperature:	<b>standard</b> -10 °C ~ 55 °C
Polarisation:	<b>standard</b> linear vertical
VSWR:	<b>standard</b> 2.0
<b>Physical characteristics</b>	
Housing material:	<b>standard</b> ABS
Diameter connector:	<b>standard</b> 10.00 mm
Length with tilt joint:	<b>standard</b> 143.00 mm
Length without tilt joint:	<b>standard</b> 109.70 mm
Colour:	<b>standard</b> white