

Delock WLAN 802.11 ac/a/h/b/g/n Antenna RP-SMA plug 5.5 - 9 dBi omnidirectional with tilt joint black

Description

This Wireless LAN antenna can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals.



RP-SMA

Specification

- Connector: RP-SMA plug
- Frequency range:
2.400 - 2.500 GHz
5.150 - 5.875 GHz
- Antenna gain:
5.5 dBi @ 2.400 - 2.500 GHz
9.0 dBi @ 5.150 - 5.875 GHz
- Impedance: 50 Ohm
- Polarisation: linear, vertical
- VSWR: 2.0
- Operating temperature: -10 °C ~ 55 °C
- Housing material: ABS
- Colour: black
- Length:
ca. 296.10 mm (with tilt joint)
ca. 245.00 mm (without tilt joint)
- Diameter:
ca. 28.00 mm (max.)
ca. 13.00 mm (RP-SMA)

System requirements

- Device with a free RP-SMA jack

Package content

- WLAN antenna




Item no. 88991

EAN: 4043619889914

Country of origin: Taiwan, Republic of China

Package: Poly bag

Images



Interface	
connector:	standard RP-SMA plug
Technical characteristics	
Frequency range:	standard 2.400 - 2.500 GHz 5.1500 - 5.8750 GHz
Gain:	standard 5.5 dBi @ 2.400 - 2.500 GHz 9.0 dBi @ 5.150 - 5.875 GHz
Impedance:	standard 50 Ω
Operating temperature:	standard -10 °C ~ 55 °C
Polarisation:	standard linear vertical
VSWR:	standard 2.0
Physical characteristics	
Housing material:	standard ABS
Diameter:	standard 28.00 mm
Diameter connector:	standard 13 mm
Length with tilt joint:	standard 296.10 mm
Length without tilt joint:	standard 245.00 mm
Colour:	standard black