



# Delock PCI Card > 3 x external + 1 x internal FireWire A

# Description

The Delock FireWire PCI card expands a PC by three external FireWire ports and one internal FireWire port. Different FireWire devices such as external hard drives, CDR and CDRW drives, camcorders etc. can be connected to this card. By using the included low profile bracket, the PCI card can be also installed into a Mini-PC.



#### **Specification**

Connector:

external:

3 x FireWire 1394A 6 pin female

internal:

1 x FireWire 1394A 6 pin female (shared with 1st external FireWire port)

- 1 x 32-Bit PCI standard 2.2
- Chipset: LSI L-FW323-07
- Data transfer rate up to 400 Mbps
- Supports OHCI specifications V1.0 and 1.1
- · Hot Plug, Plug & Play

# System requirements

- Windows 7/7-64/8/8-64/8.1/8.1-64/10/10-64, Linux Kernel 2.6
- · PC with one free PCI slot

### Package content

- PCI card
- · Low profile bracket
- User manual

# Item no. 89443

EAN: 4043619894437

Country of origin: China

Package: Retail Box

#### **Images**











| General                     |                                 |
|-----------------------------|---------------------------------|
| Function:                   | standard                        |
|                             | Hot Plug                        |
|                             | Plug & Play                     |
| Supported operating system: | standard                        |
|                             | Linux Kernel 2.6                |
|                             | Windows 7 32-bit                |
|                             | Windows 7 64-bit                |
|                             | Windows 8 32-bit                |
|                             | Windows 8 64-bit                |
|                             | Windows 8.1 32-bit              |
|                             | Windows 8.1 64-bit              |
|                             | Windows 10 32-bit               |
|                             | Windows 10 64-bit               |
| Interface                   |                                 |
| External:                   | standard                        |
|                             | 3 x FireWire 1394A 6 pin female |
| Internal:                   | standard                        |
|                             | 1 x FireWire 1394A 6 pin female |
|                             | 1 x 32-Bit PCI standard 2.2     |
| Technical characteristics   |                                 |
| Chipset:                    | standard                        |
|                             | LSI L-FW323-07                  |
| Data transfer rate:         | standard                        |
|                             | 400 Mbps                        |
| Physical characteristics    |                                 |
| Slot bracket:               | standard                        |
|                             | low profile                     |
|                             | standard                        |