

Delock WLAN Antenna RP-SMA 802.11 ac/a/h/b/g/n 0 dBi 3 m ULA100 omnidirectional white outdoor

Description

This Delock WLAN antenna can be installed outdoors or indoors and take advantage of all two bands for WLAN.



Specification

- Connector: RP-SMA plug
- Frequency range:
 - 2400 - 2500 MHz
 - 5150 - 5875 MHz
- Antenna gain: 0 dBi
- Impedance: 50 Ohm
- Polarisation: linear vertical
- VSWR: 2.0 - 2.5
- Operating temperature: -10 °C ~ 50 °C
- Protection class: IP67
- Screw mounting 13 mm central hole
- Colour: white
- Dimension: (L x W x H): ca. 77 x 45 x 45 mm
- Cable category: coaxial
- Cable type: ULA100
- Cable attenuation:
 - 1.40 dB @ 2500 MHz per meter
 - 2.30 dB @ 5875 MHz per meter
- Cable diameter: 2,79 mm
- Cable length incl. connector: ca. 3 m

Item no. 89449

EAN: 4043619894499

Country of origin: Taiwan, Republic of China

Package: Poly bag


System requirements

- Device with RP-SMA jack

Package content

- WLAN antenna
- Screw nut

Images



General

Mounting type:	standard Screw mounting with 13 mm bore hole
Protection category:	standard IP67
Suitable for indoor:	standard yes
Suitable for outdoor:	standard yes

Interface

connector:	standard 1 x RP-SMA plug
------------	------------------------------------

Technical characteristics

Frequency range:	standard 2.400 - 2.500 GHz 4.900 - 5.875 GHz
Gain:	standard 0 dBi
Impedance:	standard 50 Ω
Operating temperature:	standard -10 °C ~ 50 °C
Polarisation:	standard linear vertical
VSWR:	standard 2.0 - 2.5

Physical characteristics

Cable category:	standard coaxial
Cable type:	standard ULA 100
Cable attenuation:	standard 1.4 dB @ 2.500 GHz pro Meter 2.3 dB @ 5.875 GHz pro Meter
Cable colour:	standard white
Cable length:	standard 3 m (incl. connectors)
Cable diameter:	standard 2.79 mm
Diameter:	standard 45 mm
Height:	standard 77 mm



Colour: **standard**
white