



# Delock WLAN 802.11 b/g/n Antenna SMA Plug 3 dBi omnidirectional with connection cable (RG-174, 3 m) roof mount outdoor black

#### Description

This antenna by Delock allows the usage of the 2.4 GHz frequency range indoors and outdoors. It is completely compatible to Bluetooth and ZigBee 2.4 GHz.



### **Specification**

- Connector: 1 x SMA plug
- Frequency range: 2.4 GHz 2.5 GHz
- ZigBee 2.4 GHz, Bluetooth
- · Antenna gain: 3 dBi
- Impedance: 50 Ohm
- · Polarisation: linear, vertical
- VSWR: 2.0
- Transmission power: 10 W
- Operating temperature: -30 °C ~ 70 °C
- · Colour: black
- Housing: ABS UV resistant
- · Screw mounting with 13.5 mm hole diameter
- Thread length: ca. 18 mm
- Protection class: IP67
- · Cable: coaxial
- Cable type: RG-174
- · Cable color: black
- Cable loss: ca. 1.5 dB @ 1.5 GHz per meter
- Cable diameter: ca. 2.7 mm
- Cable length incl. connector: ca. 3 m
- Dimensions (LxD): ca. 75.0 x 53.5 mm

# System requirements

· Device with a free SMA jack

## Package content

Antenna

#### Item no. 89534

EAN: 4043619895342

Country of origin: Taiwan, Republic of


China


Package: Poly bag





## **Images**









General	
Mounting type:	standard
	Screw mounting with 12.5 mm hole diameter
Protection category:	standard
	IP67
Suitable for outdoor:	standard
	yes
Interface	
connector:	standard
	1 x SMA plug
Technical characteristics	
Frequency range:	standard
	2.400 - 2.500 GHz
Antenna gain:	standard
	3 dBi
Gain:	standard
	3 dBi
Impedance:	standard
Operating temperature	50 Ω standard
Operating temperature:	-30 °C ~ 70 °C
Polarisation:	standard
i dansalion.	linear vertical
Power handling:	standard
. The range	10 W
VSWR:	standard
	2.0
Physical characteristics	
Antenna type:	standard
	omnidirectional
Cable category:	standard
	coaxial
Cable type:	standard
	RG-174 U
Cable attenuation:	standard
	1.5 dB @ 1.5 GHz per meter
Cable colour:	standard
	black
Cable diameter:	standard
	2.7 mm
Cable length incl. connector:	standard
0.1	3 m
Colour:	standard
	black





Thread type:	standard
	M12
Dimensions (LxØ):	standard
	75.0 x 53.5 mm