



Delock PCI Express Card > 3 x external FireWire B + 1 x internal FireWire A

Description

This PCI Express card by Delock expands the PC by three external FireWire 800 ports as well as one internal FireWire 400 port. Different FireWire devices such as external enclosure, digital cameras, camcorders, adapters etc. can be connected to this card.



Specification

· Connectors:

external:

3 x FireWire 1394B 9 pin female

internal:

1 x PCI Express x1, V1.0a

- 1 x FireWire 1394A 6 pin female
- 1 x 9 pin pin header (shared with internal FireWire A)
- Chipset: Texas Instruments
- · Data transfer rate:

FireWire A up to 400 Mbps

- FireWire B up to 800 Mbps
- Supports OHCI specifications V1.0 and 1.1
- Hot Swap, Plug & Play

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, ex Linux Kernel 2.6.x / Kernel 4.9.x
- PC with one free PCI Express slot

reWire A + FireWire B PCI Express Card

Package content

- PCI Express card
- Driver CD

Images

User manual







Item no. 89864

EAN: 4043619898640

Country of origin: China

Package: Retail Box





General	
Function:	standard
	Hot Plug
	Hot Swap
Supported operating system:	standard
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Linux Kernel 2.6 or above
Interface	
External:	standard
	3 x FireWire 1394B 9 pin female
Internal:	standard
	1 x FireWire 1394A 6 pin female
	1 x PCI Express x1, V1.0a
Technical characteristics	
Chipset:	standard
	Texas Instruments
Physical characteristics	
Slot bracket:	standard

www.tragant.de 89864