

Delock Adapter RP-SMA plug to SMA jack 10 GHz

Description

This adapter by Delock is suitable for connecting components of radio frequency technology.



Specification

- Connectors:
 - 1 x RP-SMA plug >
 - 1 x SMA jack
- Housing: brass gold plated
- Thread type: 1/4" - 36 UNS - 2A
- Inner thread: 1/4" - 36 UNS - 2B
- Frequency range: 10 GHz
- Impedance: 50 Ohm
- Operating temperature: -10 °C ~ 50 °C
- Dimensions (LxD): ca. 18.1 x 7.0 mm

System requirements

- Device with one free RP-SMA or SMA port

Package content

- Adapter

Item no. 89976

EAN: 4043619899760

Country of origin: Taiwan, Republic of China

Package: Poly bag

**Interface**

Connector 1:	standard 1 x RP-SMA plug
Connector 2:	standard 1 x SMA jack

Technical characteristics

Frequency range:	standard 10 GHz
Operating temperature:	standard -10 °C ~ 50 °C

Physical characteristics

Housing material:	standard Brass gold plated
Diameter:	standard HEX 8 mm , max. 7 mm
Length:	standard 18.1 mm
Thread type:	standard 1/4" - 36 UNS - 2A 1/4" - 36 UNS - 2B