

## Delock Adapter RP-SMA plug to RP-SMA jack 10 GHz

### Description

This adapter by Delock is suitable for connecting components of radio frequency technology.



### Specification

- Connectors:
  - 1 x RP-SMA plug >
  - 1 x RP-SMA jack
- Housing: brass gold plated
- Thread type: 1/4" - 36 UNS - 2A
- Frequency range: 10 GHz
- Impedance: 50 Ohm
- Operating temperature: -10 °C ~ 50 °C
- Dimensions (LxD): ca. 17.25 x 8.00 mm

### System requirements

- Device with a free RP-SMA connector

### Package content

- Adapter

Item no. 89977

EAN: 4043619899777

Country of origin: Taiwan, Republic of China

Package: Poly bag

Interface	
Connector 1:	<b>standard</b> 1 x RP-SMA plug
Connector 2:	<b>standard</b> 1 x RP-SMA jack
Technical characteristics	
Frequency range:	<b>standard</b> 10 GHz
Operating temperature:	<b>standard</b> -10 °C ~ 50 °C
Physical characteristics	
Housing material:	<b>standard</b> Brass gold plated
Diameter:	<b>standard</b> 8.0 mm
Length:	<b>standard</b> 17.25 mm
Thread type:	<b>standard</b> 1/4" - 36 UNS - 2A