
# **Premium Pigtails**



Our premium low loss range of pigtails are suitable for telecom, datacom, data center and some critical applications. The pigtails provide 900  $\mu$ m buffered fiber for ease of handling in fiber management such as panels, splice cassettes and wall boxes.

The pigtails are terminated with premium range physical contact (single mode & multimode) and angled physical contact (single mode) zirconia ferrule connectors which are manufactured with precision factory mounting and polishing techniques which helps assure high transmission quality

### **FEATURES/BENEFITS**

- Exceed IEC performance requirements
- Easy to strip pigtails for on site installation
- Available in different fiber types
- Available with different connector types
- Provided in individual packaging or in packs of 12 x color easy strip pigtails as per IEC 60304
- Tight buffer or Easy Strip buffer low smoke zero halogen (LSZH) material with 900 micron diameter
- REACH & SvHC compliant
- Materials compliant to RoHS2

#### **APPLICATIONS**

- Patch panels, wall boxes, ODFs and splice cassettes
- Enterprise
- Datacom
- LAN and WAN
- FTTX
- · Broadband network

## **SPECIFICATIONS**

OPTICAL PERFORMANCE	SINGLE MODE	MULTIMODE	CONFORMANCE
IL (maximum - factory tested)	0.15 dB	0.15 dB	IEC 61300-3-4
Average/Random	0.12 dB	0.10 dB	IEC 61300-3-34
Return Loss (Min)	55/65 dB	20 dB*	IEC 61300-3-6

<sup>\*</sup>Return Loss based on sample data

## **Cable Specification**

CHARACTERISTICS	UNITS	SIMPLEX	
Crush	N/100 mm	500	
Operating Temperature	°C	-20 to 60	
Stripping Length - Easy Strip	m	1.5 minimum	
Stripping Length - Tight buffer	mm	30 nominal	
Nominal buffer Diameter	μm	900 ± 50	
Max Tensile Load	N	6	

### **ORDERING INFORMATION**

Code	Fibre Type Cable Type			Fiber Count Co			Color	Grade	Connector		Code		Unit	Length			
Р	9	G.652D	AA	Easy Strip	1	Single Pigtail	L	6	WHITE	Р	AX	LC	-0000-	Single Pigtail	M Meters	1	1
	7	G.657A1	AC	Tight Buffered	В	Pack of 12		Н	12 Colours		вх	LCA	-0002-	12 in one Bag		2	2
	1	OM1								'	DX	SC			_		_
	2	OM2									EX	SCA					
	3	ОМЗ									НХ	FC					
	4	OM4									JX	FCA					
											KX	ST					

#### <u>Legacy Ordering Information</u>

Connec	tor End	Fib	er Type	Cable Configuration	С	able Length		Cable Construction	
FC	FC	09	051/052	В	1	1 metre	Leave Blank	Tight Buffer	-P
LC	LC	62	OM1		2	2 metre	EASY	Easy strip	
SC	SC	50	OM2				-12/1B	Tight Buffer - Pack of 12 colours	
ST	ST	ОМЗ	ОМЗ				E-12/1B	Easy strip - Pack of 12 colours	
FCA	FC/A	OM4	OM4						
LCA	LC/A	7A1	G.657A1						
SCA	SC/A								

### **Example Part Number**

This part number has created a premium 1 metre SC SM white pigtail.



## **FURTHER INFORMATION**

- For additional information please contact your sales representative
- To view the product 360 visit the product page (Scan the QR code or visit the link below)
- Downloaded from https://www.aflhyperscale.com/product/premium-pigtails
- · AFL Hyperscale reserves the right to make changes in this datasheet at any time without notice
- Information in this document is correct as of January 08, 2020

Middle East & Africa