



30m Cat.6 S/FTP Cable, Grey

No.: 47711

RJ45, M/M, 250MHz, Copper, 27AWG

Description

- Twisted Pair Patch Cable with RJ45 connectors
- Cat.6 S/FTP PIMF, PVC
- Integrated snagless connector for latch protection
- Gold plated pins for better conductivity and elimination of signal loss
- 10 year warranty

Lindy's Cat.6 Patch Cables are manufactured and tested to conform with the ISO 11801 specification. A robust snagless strain relief design prevents damage

to the connector latch during installation and removal. Gold plated pins ensure complete signal integrity no matter the application.

Each cable is packaged in a polybag, Cables of various colours are also available and therefore ideally suited for structured cabling in server cabinets or wall cabinets.

RJ45 connectors offer universal connectivity to computers and network components, such as routers, switches, network printers and network attached storage devices.

These cables are also ideal for use in data centres, rack spaces, server rooms and network cabinets. Additional uses include security systems and AV installations.

Technical details

Connectors

- Connector A: RJ45 Male
 Connector B: RJ45 Male
- · Housing Material: Polycarbonate
- Connector Plating: Nickel
- Pin Construction: Copper Alloy
 Pin Plating: Gold plated
- Dimensions (approx.) WxDxH: 11.6x22.8x8.3mm (0.46x0.90x0.33in)

Cable Construction

- Length: 30m (98.43ft)
- Colour: Grey
- Type: Cat.6
- Jacket Diameter: 6.2mm (0.24in)
- Jacket Material: PVC

- Conductor Material: Copper
 Conductor Gauge: 27AWG
 Shielding: Aluminium Braid

Specifications

- Supported Bandwidth: 250MHz
 Nominal Attenuation: 32.8dB/100m @250MHz
- Minimum Band Radius: 74mm (2.91in)
 Operating Temperature: -10°C 60°C (14°F 140°F)
 Storage Temperature: -20°C 75°C (-4°F 167°F)

Miscellaneous

- Packaging Type: Polybag
 Warranty (Years): 10
 Certificated: RoHS, REACH, UL, California Proposition 65

Purchasing Information

- No.: 47711
 - EAN: 4002888477116

This product is also available in other lengths

- 47700 0.3m (0.98ft)
 47701 0.5m (1.64ft)
 47702 1m (3.28ft)
 47703 1.5m (4.92ft)

- 47704 2m (6.56ft)
 47705 3m (9.84ft)

- 47705 3fm (9.64ff)
 47706 5m (16.44ft)
 47707 7.5m (24.61ft)
 47708 10m (32.81ft)
 47709 15m (49.21ft)
 47710 20m (65.62ft)
 47714 20m (65.42ft)
- 47711 30m (98.43ft)

© LINDY 2019