



Delock GSM Antenna SMA plug 3.5 dBi fixed omnidirectional with magnetic base and connection cable RG-174 3 m outdoor black

Description

This GSM antenna by Delock allows the usage of different GSM bands inside and outside. It is completely compatible to GSM, UMTS, ZigBee 868 MHz / 915 MHz, DECT, Z-Wave and LoRa 868 MHz / 915 MHz.



Specification

- Connector: 1 x SMA plug
- Frequency range:
824 - 960 MHz
1710 - 2200 MHz
- GSM, UMTS, ZigBee 868 MHz / 915 MHz, DECT, Z-Wave, LoRa 868 MHz / 915 MHz
- Antenna gain: 3.5 dBi
- Impedance: 50 Ohm
- Polarisation: vertical
- VSWR: 2.0
- Transmission power: 10 W
- Operating temperature: -30 °C ~ 70 °C
- Colour: black
- Cable: coaxial
- Cable type: RG-174
- Cable colour: black
- Cable attenuation: 1.5 dB @ 1.5 GHz per meter
- Cable diameter: ca. 2.7 mm
- Cable length incl. connector: ca. 3 m
- Antenna length including magnetic base: ca. 38.4 cm
- Diameter magnetic base: ca. 50.0 mm

Item no. 12423

EAN: 4043619124237

Country of origin: Taiwan, Republic of China

Package: Poly bag



System requirements

- Device with a free SMA jack

Package content

- GSM antenna

Images





General	
Mounting type:	standard magnet
Protection category:	standard without
Interface	
connector:	standard 1 x SMA plug
Technical characteristics	
Frequency range:	standard 1710 - 2200 MHz 824 - 960 MHz
Antenna gain:	standard 3.5 dBi
Impedance:	standard 50 Ω
Operating temperature:	standard -30 °C ~ 70 °C
Polarisation:	standard vertical
Power handling:	standard 10 W
VSWR:	standard 2.0
Physical characteristics	
Antenna type:	standard omnidirectional Rod antenna
Antenna length incl. magnetic base:	standard 384 mm
Diameter magnetical base:	standard 50 mm
Thread length:	standard 8 mm
Cable type:	standard RG-174
Cable length incl. connector:	standard 3 m
Diameter connector:	standard 8.5 mm
Colour:	standard black
Thread type:	standard M5