



Delock USB Condenser Microphone Omnidirectional for Conferences

Description

This table microphone by Delock is suitable for use in conferences.

Optimal recordings

The microphone has a circle pattern (omnidirectional) and therefore captures the acoustic signal ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

Touch mute button & status LED

The touch mute button quickly mutes the microphone. The LED is red when muted and green when recording.

Headphone output

The microphone has a 3.5 mm stereo jack output for connecting headphones or speakers.

Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.



1,5 m

Specification

- Connectors:
 - 1 x USB 2.0 Type-A male
 - 1 x 3.5 mm 3 pin stereo jack female
- Directivity: omnidirectional
- Sensitivity: -16 dB +/- 3 dB
- Frequency range: 100 Hz - 10 kHz
- Sample rate: 16 Bit / 44.1 kHz
- Signal-to-noise ratio (SNR): ca. 65 dB
- Mute-Button
- Status LED
- Cable length: ca. 1.5 m
- Colour: black
- Dimensions (Ø x H): ca. 75 x 19 mm
- USB bus powered
- Plug & Play

System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- User manual

Item no. 20672

EAN: 4043619206728

Country of origin: China

Package: Retail Box



Images





General	
Function:	standard Plug & Play
Supported operating system:	standard Chrome OS Linux Kernel 4.4 or above Mac OS 10.9 or above Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit
LED indicator:	standard 1 x
Interface	
connector:	standard 1 x USB 2.0 Type-A male
Technical characteristics	
Frequency range:	standard 100 Hz - 10 kHz
Voltage:	standard USB bus powered
Sensibility:	standard -16 dB +/- 3 dB
Sample rate:	standard 16 Bit / 44.1 kHz
Signal noise ratio (SNR):	standard ca. 65 dB
Directivity:	standard omnidirectional
Physical characteristics	
Cable length:	standard 1.5 m
Diameter:	standard 75 mm
Height:	standard 19 mm
LED colour:	standard red green