



PICABOND® Connector, 250 loose piece, 400 Vdc, yellow

- Lightweight, compact, and economical means of splicing multiconductor telephone cable
- No prestripping or cutting required, can tap without service interruptions, eliminates “turndowns”
- Color-coded to indicate size and type of wire; used for butt, straight, bridge and half-tap splicing applications

Product Classification

Brand	PICABOND®
Product Type	Splice
Product Series	PICABOND
Regional Availability	Australia/New Zealand EMEA Latin America North America

Electrical Specifications

Safety Voltage Rating	400 Vdc
------------------------------	---------

Environmental Specifications

Environmental Space	Outdoor
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)

General Specifications

Connector Color Code	Yellow
Connector Sealant	Gel filled
Connector Splicing Type	Bridge Butt Full bridge Half-tap Straight (In-line)
Insulation Material	Air Core PIC Foam Filled PIC
Package Quantity	250
Packaging Type	Loose piece

Mechanical Specifications

Conductor Gauge, solid	24–19 AWG
Contact Base Material	Phosphor bronze
Contact Plating Material	Tin

Regulatory Compliance/Certifications

Agency
RoHS 2011/65/EU

Classification
Compliant