

Navilock NL-442U USB 2.0 GPS Receiver SiRFstarIV™

Description

The USB 2.0 GPS Receiver based on SiRFstarIV™ chipset has a built-in antenna for high sensitivity. You can use this GPS Receiver with a notebook and a suitable routing software for navigation.



Specification

- SiRFstarIV™ GSD4e chipset
- Frequency: L1, 1575.42 MHz, C/A Code: 1.023 MHz
- Accepts the signals of up to 48 satellites at the same time
- Supports WAAS, EGNOS and MSAS
- Supports NMEA 0183 V3.0 protocols: GGA, GSA, GSV, RMC, VTG, GLL v2.2 (VTG and GLL are optional)
- USB specification 2.0
- 4800 baud rate
- Update rate: 1 Hz
- Datum: WGS-84
- Sensibility max. -163 dBm
- IPX6 protection class
- Magnatic, non-slip on the bottom
- LED-indicator for GPS-status
- Operating temperature: -20 °C to +65 °C
- Cold start in about 35 sec.
- Hot start in about 1 sec.
- Positioning accuracy: < 2.5 m 2D RMS SBAS Enable
- Dimension (LxWxH): 65 mm x 45 mm x 22 mm

System requirements

- Windows 2000/XP/Vista/7/8/8.1/10, Linux ab Kernel 2.6, Mac OS 10.6.x, 10.7.x
- PC or Notebook with a free USB port

Package content

- USB 2.0 Receiver
- Driver CD
- User manual on CD ROM

Item No. 61994

EAN: 4043619619948

Country of origin: Taiwan, Republic of China

Package: Retail Box



Images



