

Delock Audio Converter Analogue > Digital

Description

The audio converter by Delock converts an analogue stereo signal into a digital signal. Two cinch cables can be connected to the device to input the analog source signal, e. g. from an MP3 player. At the output, the signal can be transmitted either via optical TOSLINK connection or via S/PDIF coaxial connection.



Specification

- Connectors:
Input:
2 x RCA female
1 x DC jack
Output:
1 x TOSLINK female S/PDIF
1 x Coaxial female S/PDIF
- Sample rate: 16 Bit / 48 kHz
- Robust metal housing
- Dimensions (LxWxH): ca. 63 x 41 x 21 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.5 A
- Output: 5 V / 2 A
- Ground outside, plus inside
- Dimensions:
inside: ø ca. 2.1 mm
outside: ø ca. 5.5 mm
length: ca. 9 mm

System requirements

- Analogue audio signal
- Connection cable

Package content

- Converter analogue > digital
- Power supply
- User manual

Item no. 62443

EAN: 4043619624430

Country of origin: China

Package: White Box

Images





Interface	
Output:	standard 1 x Coaxial female S/PDIF 1 x TOSLINK female S/PDIF
Input:	standard 2 x RCA female (red, white) 1 x 5 V DC female 5,5 mm x 2,1 mm
Physical characteristics	
Housing colour:	standard black
Housing material:	standard Plastic
Length:	standard 63 mm
Width:	standard 41 mm
Height:	standard 21 mm