



Delock USB 3.1 Gen 1 Adapter USB Type-C™ male > 2 x USB 3.0 Type-A female + 1 x HDMI female (DP Alt Mode) 4K 30 Hz

Description

This adapter by Delock is suitable for the connection to a computer with USB-C™ interface and Displayport alternate mode support. It extends the system by two USB 3.0 Type-A interfaces as well as one HDMI interface. The adapter has a USB Type-C™ Power Delivery port. This allows the laptop to be charged while the adapter is in use, as well as providing additional power to the two USB Type-A connectors.



Specification

- Connectors:
 - 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ male >
 - 2 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female
 - 1 x HDMI-A 19 pin female
 - 1 x USB Type-C™ Power Delivery female (optional for power supply)
- Chipset: Parade PS176 + VIA VL812
- Displayport 1.2, High Speed HDMI with Ethernet (HEC) and SuperSpeed USB specification
- HDMI specification:
 - Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
 - Transfer of audio and video signals
 - Supports 3D displays
 - Supports HDCP 1.4 and 2.2
- USB bus powered
- Plug & Play
- 1 x ferrite core
- Cable length without connectors: ca. 15 cm
- Colour: black

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.4.x, Mac OS 10.11
- PC or laptop with a free USB Type-C™ port and Displayport alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- USB-C™ to 2 x USB-A + HDMI Adapter

Item no. 62854

EAN: 4043619628544

Country of origin: China

Package: Retail Box

Images



General	
Function:	standard Plug & Play
Specification:	standard SuperSpeed USB (USB 3.1 Gen 1) Displayport 1.2 High Speed HDMI with Ethernet HDCP 1.4 HDCP 2.2
Supported operating system:	standard Linux ex Kernel 4.x.x Mac 10.11 Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit
Interface	
Output:	standard 2 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female 1 x HDMI-A 19 pin female
Input:	standard 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ male
Technical characteristics	
Chipset:	standard VIA VL812 Parade PS176
Maximum screen resolution:	standard 3840 x 2160 @ 30 Hz
Signal transmission:	standard video audio
Voltage:	standard USB bus powered 1 x USB Type-C™ Power Delivery female (optional for power supply)
Physical characteristics	
Ferrite core:	standard 1 x
Cable length:	standard 15 cm
Connector finishing:	standard gold-plated
Colour:	standard black

