

# Delock Adapter USB Type-C™ male > VGA female (DP Alt Mode) with PD function

## Description

This Delock adapter is suitable for the connection of a VGA monitor to a computer with USB-C™ interface and Displayport alternate mode support. Thus, the adapter can be connected to different laptops like Macbook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface. The adapter has a USB Type-C™ Power Delivery port. This allows the laptop to be charged while the adapter is in use.



## Specification

- Connectors:
  - Input:
    - 1 x USB Type-C™ male
    - 1 x USB Type-C™ Power Delivery female (optional for power supply)
  - Output:
    - 1 x VGA 15 pin female
- Chipset: VIA VL100 + ITE IT6516
- VGA port with nuts
- Resolution up to WUXGA 1920 x 1200 @ 60 Hz (depending on the system and the connected hardware)
- Transfer of analogue video signals
- Charging power: max. 60 W, 20 V @ 3 A
- USB bus powered
- Plug & Play
- Housing material: aluminium
- 1 x ferrite core
- Cable length without connectors: ca. 20 cm
- Colour: dark grey

## System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.3, Mac ex OS 10.12
- PC or laptop with a free USB Type-C™ port and Displayport alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

## Package content

- USB-C™ to VGA adapter

## Item no. 62989

EAN: 4043619629893

Country of origin: China

Package: Retail Box

## Images





|                             |                                                                                                                                                                                         |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General                     |                                                                                                                                                                                         |
| Function:                   | <b>standard</b><br>Plug & Play                                                                                                                                                          |
| Supported operating system: | <b>standard</b><br>Windows 7 32-bit<br>Windows 7 64-bit<br>Windows 8.1 32-bit<br>Windows 8.1 64-bit<br>Windows 10 32-bit<br>Windows 10 64-bit<br>ex Linux Kernel 4.3<br>ex Mac OS 10.12 |
| Interface                   |                                                                                                                                                                                         |
| Output:                     | <b>standard</b><br>1 x VGA 15 pin female                                                                                                                                                |
| Input:                      | <b>standard</b><br>1 x USB Type-C™ female (power supply)<br>1 x USB Type-C™ male                                                                                                        |
| Technical characteristics   |                                                                                                                                                                                         |
| Chipset:                    | <b>standard</b><br>VIA VL100<br>ITE IT6516                                                                                                                                              |
| Maximum screen resolution:  | <b>standard</b><br>1920 x 1200 @ 60 Hz                                                                                                                                                  |
| Signal transmission:        | <b>standard</b><br>video                                                                                                                                                                |
| Physical characteristics    |                                                                                                                                                                                         |
| Ferrite core:               | <b>standard</b><br>1 x                                                                                                                                                                  |
| Housing material:           | <b>standard</b><br>Aluminium                                                                                                                                                            |
| Cable length:               | <b>standard</b><br>20 cm                                                                                                                                                                |
| Connector finishing:        | <b>standard</b><br>nickel-plated                                                                                                                                                        |
| Colour:                     | <b>standard</b><br>dark grey                                                                                                                                                            |