



Delock Active DisplayPort 1.2 to HDMI Cable 4K 60 Hz 2 m

Description

This cable by Delock enables the connection between devices, e.g. a monitor, with HDMI connector to a DisplayPort interface.

Active cable

The cable offers an active conversion, thus it is also suitable for graphics cards that are not capable of outputting DP++ signals.

**2 m**

Specification

- Connectors:
 - 1 x DisplayPort male >
 - 1 x HDMI-A male
- Signal direction: DisplayPort input > HDMI output
- Chipset: Parade PS176
- DisplayPort 1.2 and High Speed HDMI specification
- Cable gauge: 28 AWG
- Cable diameter: ca. 7.2 mm
- Contacts gold-plated
- Active cable, for graphics cards with DP and DP++ output
- Transmission of audio and video signals
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Supports 3D displays (1080p @ 120 Hz)
- Supports HDCP 1.3
- Supports Eyefinity
- 2 x ferrite core
- Colour: black
- Length incl. connectors: ca. 2 m

System requirements

- A free DisplayPort female

Package content

- DisplayPort to HDMI cable

Item no. 85956

EAN: 4043619859566

Country of origin: China

Package: Zip poly bag

Images





General	
Specification:	standard DisplayPort 1.2 High Speed HDMI
Interface	
Connector 1:	standard 1 x DisplayPort male
Connector 2:	standard 1 x HDMI-A male
Technical characteristics	
Chipset:	standard Parade PS176
Maximum screen resolution:	standard 3840 x 2160 @ 60 Hz
Physical characteristics	
Ferrite core:	standard 2 x
Pin finishing:	standard gold-plated
Conductor material:	standard copper
Conductor gauge:	standard 28 AWG
Shielding:	standard triple
Diameter:	standard 7.2 mm
Length:	standard 2 m
Colour:	standard black