



Delock Multi-AV to HDMI Converter 4K 60 Hz for table mount

Description

This multi-functional converter by Delock makes it possible to convert different sources into one HDMI signal. The signal inputs are USB-C™ (DP Alt Mode), VGA with 3.5 mm audio, Mini DisplayPort and HDMI. The converter box is a practical solution for connecting various audio / video devices to a projector or TV with HDMI input.



Specification

- Connectors:
 - Input:
 - 1 x mini DisplayPort 20 pin female
 - 1 x HDMI-A 19 pin female
 - 1 x USB Type-C™ (DP Alt Mode) female
 - 1 x VGA 15 pin female with nuts
 - 1 x 3.5 mm 3 pin stereo jack female
 - 1 x DC 24 V power connector screwable
 - 1 x RJ45 jack
 - Output:
 - 1 x HDMI-A 19 pin female
 - 1 x USB Type-C™ female with BC1.2 5 V / 2.4 A
 - 1 x USB Type-A female with BC1.2 5 V / 2.4 A
 - 1 x RJ45 jack
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Resolution (VGA input) up to 1920 x 1080 @ 60 Hz
- Transmission of audio and video signals
- Switching automatic or via button
- Robust metal housing
- Dimensions (LxWxH): ca. 184 x 96 x 80 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 1 A
- Output: 24 V / 1.5 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 9.5 mm

Package content

- Converter
- Mounting bracket
- Power supply
- User manual

Item no. 87733

EAN: 4043619877331

Country of origin: Taiwan, Republic of China

Package: White Box



Images





General	
Mounting type:	standard in-desk
Interface	
Output:	standard 1 x USB Type-A female 5 V / 2.4 A 1 x RJ45 jack 1 x HDMI-A 19 pin female 1 x USB type-C™ female 5 V / 2.4 A
Input:	standard 1 x HDMI-A 19 pin female 1 x mini DisplayPort 20 pin female 1 x 3.5 mm 3 pin stereo jack female 1 x RJ45 jack 1 x USB type-C™ female 1 x VGA 15 pin female 1 x DC female
Technical characteristics	
Maximum screen resolution:	standard 3840 x 2160 @ 60 Hz
Physical characteristics	
Length:	standard 184 mm
Width:	standard 96 mm
Height:	standard 80 mm